

● 产品特征 Features

符合环保要求
 RoHS compliant, REACH Compliant, HF
 扁平线绕线结构, 超低内阻
 Flat wire structure, ultra-low resistance
 超大电流承载能力, 优异的热稳定性
 High current carrying capacity; Excellent thermal stability.
 精准阻抗有效抑制电磁干扰
 Prevent EMI effect via precise impedance

● 产品应用 Applications

高电流要求驱动电路滤波
 Drive circuit filtering of high currents require
 电源电路直流-直流转换
 DC-DC conversion for power circuit



● 命名方式 Part Numbering

GAF F 069030HMT 1R0

类型/Type

GAF 产品系列
 Product Type

铜线形状/Conductor Geometry

F 扁平/Flat

封装尺寸/Dimension

70033 请参考系列产品尺寸
 Refer to the dimensions of the series

外观代码/Visual identification

H 高性能品
 Performance Series

电感公差/Acceptable tolerance

M ±20% N ±30%


包装方式/Packaging Code

T/Taping Reel


标称电感/Nominal inductance value

47N	47.0nH	5R6	5.60μH
R22	0.22μH	100	10.0μH

● 产品结构 Structure




● 电气原理 Schematic diagram



● 外观尺寸 Mechanical Dimensions

(Units:mm)



项目Item 产品系列Part No.	A	B	C	D	E	F	G	H	I
GAFF069030H	7.0±0.5	6.9±0.3	3.0±0.3	1.4±0.3	1.8±0.3	0~0.2	2.70Typ.	2.40Typ.	2.20Typ.
GAFF069040H	7.0±0.5	6.9±0.3	3.7±0.3	1.4±0.3	1.8±0.3	0~0.2	2.70Typ.	2.40Typ.	2.20Typ.
GAFF069050H	7.0±0.5	6.9±0.3	4.7±0.3	1.4±0.3	1.8±0.3	0~0.2	2.70Typ.	2.40Typ.	2.20Typ.
GAFF102030H	11.2Max	10.2±0.5	3.0±0.3	2.0±0.3	2.5±0.5	0~0.2	3.85Typ.	3.80Typ.	4.00Typ.
GAFF102040H	11.2Max	10.2±0.5	4.0±0.3	See table	2.5±0.5	0~0.2	3.85Typ.	3.80Typ.	4.00Typ.
GAFF102050H	11.2Max	10.2±0.5	4.7±0.3	See table	2.5±0.5	0~0.2	3.85Typ.	3.80Typ.	4.00Typ.
GAFF102060H	11.2Max	10.2±0.5	5.7±0.3	See table	2.5±0.5	0~0.2	3.85Typ.	3.80Typ.	4.00Typ.
GAFF128035H	13.8Max	12.8±0.5	3.2±0.3	See table	3.0±0.5	0~0.2	4.50Typ.	6.00Typ.	5.00Typ.
GAFF128050H	13.8Max	12.8±0.5	4.7±0.3	See table	3.0±0.5	0~0.2	4.50Typ.	6.00Typ.	5.00Typ.
GAFF128065H	13.8Max	12.8±0.5	6.2±0.3	See table	3.0±0.5	0~0.2	4.50Typ.	6.00Typ.	5.00Typ.
GAFF128075H	13.8Max	12.8±0.5	7.3±0.3	See table	3.0±0.5	0~0.2	4.50Typ.	6.00Typ.	5.00Typ.
GAFF160070H	16.8Max	16.0±0.5	6.7±0.3	3.2±0.5	3.5±0.5	0~0.3	5.00Typ.	8.00Typ.	4.50Typ.
GAFF182090H	19.3Max	18.2±0.5	8.9±0.3	See table	4.5±0.5	0~0.3	6.00Typ.	7.30Typ.	6.00Typ.
GAFF220120H	22.5±1.0	22.0±0.5	12.0±0.4	See table	5.5±1.0	0~0.3	7.00Typ.	9.50Typ.	5.50Typ.

● 产品特性Electrical Specifications

说明Illustrate

1.所有参数均在25±3°C条件下测得，电感值测试频率100KHz/0.1V

All of the electrical specifications are test at 25°C, inductance test at 100KHz/0.1V.

2.温升电流是指在25°C环境下，导致器件表面温度上升约40°C时加载的直流电流值

I_{rms} is the current that caused a approximate 40°C temperature rise from 25°C ambient.

3. 饱和电流是指导致初始电感量下降约30%时的直流电流值

I_{sat} is the DC current at which inductance drop approximately 30% from its value without current.

4. 在最严苛条件下，器件温度（含自身温升）不应超过+125°C。电路设计、元件布局、PCB走线尺寸和厚度、空气流动以及其他散热措施都会影响部件温度，应在最终应用中验证部件温度。

The part temperature(ambient + temp.rise) should not exceed 125°C under worst case operating conditions. Circuit design,component placement,PCB trace size and thickness,airflow and other cooling provisions all affect the part temperature.Part temperature should be verified in the end appliction.

5.由于产品改进，产品规格可能会不定期更改，恕不另行通知。

Due to product improvement, the specifications may be changed discontinuously without advance notice.

GAFF069030H SERIES

规格型号 Part Number	初始电感 (μH)	DCR (mΩ)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF069030HMTR10	0.10±20%	0.78	0.90	23.0	70.0	/
GAFF069030HMTR22	0.22±20%	1.58	1.82	19.0	48.0	/
GAFF069030HMTR47	0.47±20%	3.40	3.91	14.5	34.0	/
GAFF069030HMT1R0	1.00±20%	5.63	6.50	11.5	18.5	/
GAFF069030HMT1R5	1.50±20%	7.90	9.10	8.70	15.0	/
GAFF069030HMT2R2	2.20±20%	10.8	12.4	7.80	12.0	/

GAFF069040H SERIES

规格型号 Part Number	初始电感 (μH)	DCR (mΩ)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF069040HMTR24	0.24±20%	1.00	1.20	21.0	45.0	/
GAFF069040HMTR47	0.47±20%	1.66	1.90	19.0	35.0	/
GAFF069040HMTR68	0.68±20%	2.72	3.20	17.5	30.0	/
GAFF069040HMT1R0	1.00±20%	3.90	4.50	15.5	24.0	/
GAFF069040HMT1R5	1.50±20%	5.40	6.20	11.5	18.0	/
GAFF069040HMT2R2	2.20±20%	10.5	12.1	9.00	16.0	/
GAFF069040HMT3R5	3.50±20%	15.0	17.3	6.80	14.0	/
GAFF069040HMT4R7	4.70±20%	18.4	21.2	6.40	11.0	/
GAFF069040HMT5R6	5.60±20%	20.1	23.0	5.50	9.50	/
GAFF069040HMT6R5	6.50±20%	31.5	36.2	4.60	8.20	/

GAFF069050H SERIES

规格型号 Part Number	初始电感 (μH)	DCR (mΩ)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF069050HMTR25	0.25±20%	0.88	1.00	21.0	60.0	/
GAFF069050HMTR47	0.47±20%	1.36	1.56	18.0	39.0	/
GAFF069050HMT1R0	1.00±20%	3.55	4.10	15.0	27.0	/
GAFF069050HMT1R5	1.50±20%	4.10	4.75	13.5	22.5	/
GAFF069050HMT2R0	2.00±20%	5.57	6.40	11.8	19.5	/
GAFF069050HMT2R7	2.70±20%	7.10	8.20	10.3	16.5	/
GAFF069050HMT3R3	3.30±20%	8.50	9.80	9.00	15.3	/
GAFF069050HMT3R9	3.90±20%	12.3	14.2	8.00	14.0	/
GAFF069050HMT4R7	4.70±20%	14.8	17.0	6.50	12.7	/
GAFF069050HMT5R6	5.60±20%	19.2	22.1	6.20	11.4	/
GAFF069050HMT6R8	6.80±20%	20.5	23.6	6.00	10.3	/

GAFF069050H SERIES

规格型号 Part Number	初始电感 (μ H)	DCR (m Ω)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF069050HMT7R6	7.60 \pm 20%	20.5	23.6	6.00	8.30	/
GAFF069050HMT8R8	8.80 \pm 20%	21.6	24.9	4.80	7.90	/
GAFF069050HMT100	10.0 \pm 20%	26.5	30.5	4.40	7.40	/
GAFF069050HMT130	13.0 \pm 20%	38.6	44.4	3.10	6.50	/

GAFF102030H SERIES

规格型号 Part Number	初始电感 (μ H)	DCR (m Ω)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF102030HMTR20	0.20 \pm 20%	0.82	0.95	22.0	65.0	/
GAFF102030HMTR47	0.47 \pm 20%	2.15	2.50	18.0	40.0	/
GAFF102030HMT1R0	1.00 \pm 20%	4.08	4.70	15.0	25.0	/
GAFF102030HMT1R5	1.50 \pm 20%	6.58	7.60	12.0	22.0	/
GAFF102030HMT2R2	2.20 \pm 20%	11.5	13.3	9.00	18.0	/
GAFF102030HMT2R5	2.50 \pm 20%	11.5	13.3	9.00	15.0	/

GAFF102040H SERIES

规格型号 Part Number	初始电感 (μ H)	DCR (m Ω)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF102040HMTR18	0.18 \pm 20%	0.61	0.70	30.0	80.0	2.50
GAFF102040HMTR38	0.38 \pm 20%	1.11	1.28	22.0	65.0	2.50
GAFF102040HMTR66	0.66 \pm 20%	1.84	2.20	18.0	50.0	2.50
GAFF102040HMT1R0	1.00 \pm 20%	3.01	3.50	16.0	41.0	2.00
GAFF102040HMT1R5	1.50 \pm 20%	4.64	5.50	14.0	33.0	2.00
GAFF102040HMT2R2	2.20 \pm 20%	6.90	7.90	11.0	28.0	2.00
GAFF102040HMT2R7	2.70 \pm 20%	6.90	7.90	11.0	22.0	2.00
GAFF102040HMT3R5	3.50 \pm 20%	8.65	10.0	9.50	19.0	2.00
GAFF102040HMT4R5	4.50 \pm 20%	11.3	13.0	8.00	16.0	2.00
GAFF102040HMT5R6	5.60 \pm 20%	13.7	15.8	7.20	14.5	2.00
GAFF102040HMT6R8	6.80 \pm 20%	20.5	23.6	5.60	13.0	2.00

GAFF102050H SERIES

规格型号 Part Number	初始电感 (μ H)	DCR (m Ω)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF102050HMTR18	0.18 \pm 20%	0.45	0.55	32.0	80.0	2.50
GAFF102050HMTR39	0.39 \pm 20%	0.67	0.77	24.0	55.0	2.50
GAFF102050HMTR82	0.82 \pm 20%	1.26	1.50	23.0	36.0	2.50
GAFF102050HMT1R2	1.20 \pm 20%	2.05	2.35	19.0	32.0	2.50
GAFF102050HMT1R8	1.80 \pm 20%	2.98	3.45	17.0	27.0	2.00
GAFF102050HMT2R5	2.50 \pm 20%	4.06	4.70	15.0	23.0	2.00
GAFF102050HMT3R3	3.30 \pm 20%	5.37	6.50	13.0	19.0	2.00
GAFF102050HMT4R2	4.20 \pm 20%	7.11	8.50	11.0	17.0	2.00
GAFF102050HMT5R6	5.60 \pm 20%	8.62	9.90	10.3	14.0	2.00
GAFF102050HMT6R8	6.80 \pm 20%	10.5	12.1	9.00	12.5	2.00
GAFF102050HMT8R2	8.20 \pm 20%	13.1	15.1	8.10	11.5	2.00
GAFF102050HMT100	10.0 \pm 20%	16.4	18.9	7.10	10.2	2.00
GAFF102050HMT150	15.0 \pm 20%	25.9	29.8	5.50	8.75	2.00
GAFF102050HMT180	18.0 \pm 20%	34.7	39.9	5.00	8.30	2.00

GAFF102060H SERIES

规格型号 Part Number	初始电感 (μ H)	DCR (m Ω)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF102060HMTR38	0.38 \pm 20%	0.67	0.77	25.0	70.0	2.50
GAFF102060HMT1R0	1.00 \pm 20%	1.65	1.90	21.0	40.0	2.50
GAFF102060HMT1R5	1.50 \pm 20%	2.47	2.85	19.0	34.0	2.50
GAFF102060HMT2R2	2.20 \pm 20%	3.60	4.20	16.0	29.0	2.50
GAFF102060HMT2R9	2.90 \pm 20%	4.45	5.15	14.0	26.0	2.00
GAFF102060HMT3R8	3.80 \pm 20%	5.89	6.77	12.0	22.0	2.00
GAFF102060HMT4R7	4.70 \pm 20%	7.08	8.15	10.8	21.0	2.00
GAFF102060HMT5R6	5.60 \pm 20%	9.23	10.6	9.60	18.0	2.00
GAFF102060HMT6R8	6.80 \pm 20%	10.9	12.5	8.70	16.5	2.00
GAFF102060HMT8R2	8.20 \pm 20%	13.6	15.6	7.80	15.0	2.00
GAFF102060HMT100	10.0 \pm 20%	16.3	18.7	6.20	12.5	2.00
GAFF102060HMT150	15.0 \pm 20%	20.9	24.0	5.60	10.5	2.00
GAFF102060HMT220	22.0 \pm 20%	31.6	36.3	4.50	8.80	2.00
GAFF102060HMT270	27.0 \pm 20%	42.2	48.5	4.00	8.00	2.00

GAFF128035H SERIES

规格型号 Part Number	初始电感 (μ H)	DCR (m Ω)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF128035HMTR25	0.25 \pm 20%	0.78	0.90	24.0	70.0	2.50
GAFF128035HMTR68	0.68 \pm 20%	1.60	1.82	22.0	45.0	2.50
GAFF128035HMT1R2	1.20 \pm 20%	2.90	3.35	17.0	32.0	2.50
GAFF128035HMT2R2	2.20 \pm 20%	5.70	6.55	14.0	22.0	2.50
GAFF128035HMT3R3	3.30 \pm 20%	8.20	9.45	12.0	18.0	2.50
GAFF128035HMT4R7	4.70 \pm 20%	11.7	13.5	9.00	15.2	2.00
GAFF128035HMT5R6	5.60 \pm 20%	19.0	21.9	6.80	14.5	2.00

GAFF128050H SERIES

规格型号 Part Number	初始电感 (μ H)	DCR (m Ω)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF128050HMTR19	0.19 \pm 20%	0.48	0.55	32.0	100	2.50
GAFF128050HMTR45	0.45 \pm 20%	0.90	1.05	26.0	72.0	2.50
GAFF128050HMTR82	0.82 \pm 20%	1.60	1.85	24.0	55.0	2.50
GAFF128050HMT1R0	1.00 \pm 20%	1.43	1.65	25.0	51.0	2.50
GAFF128050HMT1R6	1.60 \pm 20%	2.30	2.65	22.0	43.0	2.50
GAFF128050HMT2R2	2.20 \pm 20%	3.37	3.88	18.0	35.0	2.50
GAFF128050HMT3R3	3.30 \pm 20%	4.64	5.35	16.5	30.0	2.50
GAFF128050HMT4R5	4.50 \pm 20%	6.46	7.50	14.0	26.0	2.00
GAFF128050HMT5R6	5.60 \pm 20%	8.00	9.20	12.0	23.0	2.00
GAFF128050HMT6R8	6.80 \pm 20%	10.3	11.8	10.3	20.5	2.00
GAFF128050HMT8R2	8.20 \pm 20%	10.3	11.8	10.3	17.5	2.00
GAFF128050HMT100	10.0 \pm 20%	13.5	15.5	8.80	16.0	2.00

GAFF128065H SERIES

规格型号 Part Number	初始电感 (μ H)	DCR (m Ω)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF128065HMTR20	0.20 \pm 20%	0.32	0.37	36.0	>110	2.50
GAFF128065HMTR47	0.47 \pm 20%	0.65	0.75	32.0	90.0	2.50
GAFF128065HMTR85	0.85 \pm 20%	0.90	1.05	26.0	63.0	2.50
GAFF128065HMT1R3	1.30 \pm 20%	1.69	1.95	25.0	50.0	2.50
GAFF128065HMT2R0	2.00 \pm 20%	2.25	2.60	23.0	41.0	2.50
GAFF128065HMT2R7	2.70 \pm 20%	3.25	3.75	20.0	35.0	2.50
GAFF128065HMT3R6	3.60 \pm 20%	4.20	4.85	17.0	30.0	2.50
GAFF128065HMT4R7	4.70 \pm 20%	5.42	6.25	14.0	27.0	2.50

GAFF128065H SERIES

规格型号 Part Number	初始电感 (μ H)	DCR (m Ω)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF128065HMT5R8	5.80±20%	6.93	7.97	12.0	24.0	2.50
GAFF128065HMT7R3	7.30±20%	5.68	6.50	13.0	18.5	2.50
GAFF128065HMT9R2	9.20±20%	7.24	8.35	12.0	16.3	2.50
GAFF128065HMT100	11.0±20%	8.87	10.2	11.0	15.0	2.50
GAFF128065HMT130	13.0±20%	10.2	11.7	10.0	13.5	2.50
GAFF128065HMT150	15.0±20%	12.3	14.1	9.00	12.5	2.50
GAFF128065HMT180	18.0±20%	15.2	17.5	8.50	11.2	2.50
GAFF128065HMT220	22.0±20%	18.6	21.5	8.00	10.7	2.50
GAFF128065HMT270	27.0±20%	23.9	27.5	6.50	9.50	2.50
GAFF128065HMT330	33.0±20%	26.3	30.3	5.50	8.80	2.50
GAFF128065HMT390	39.0±20%	40.3	46.5	4.50	8.00	2.00
GAFF128065HMT470	47.0±20%	54.5	62.7	4.00	7.20	2.00

GAFF128075H SERIES

规格型号 Part Number	初始电感 (μ H)	DCR (m Ω)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF128075HMTR60	0.60±20%	0.48	0.55	36.0	80.0	2.50
GAFF128075HMT1R0	1.00±20%	0.84	1.00	32.0	68.0	2.50
GAFF128075HMT1R5	1.50±20%	1.40	1.61	28.0	54.0	2.50
GAFF128075HMT2R2	2.20±20%	2.10	2.45	24.0	45.0	2.50
GAFF128075HMT3R3	3.30±20%	2.70	3.10	22.0	37.0	2.50
GAFF128075HMT4R7	4.70±20%	3.68	4.25	19.0	30.0	2.50
GAFF128075HMT5R6	5.60±20%	4.60	5.30	17.0	27.0	2.50
GAFF128075HMT6R8	6.80±20%	6.05	6.95	14.0	25.5	2.50
GAFF128075HMT8R2	8.20±20%	7.03	8.10	12.0	23.0	2.50
GAFF128075HMT100	10.0±20%	8.77	10.1	11.0	21.0	2.50
GAFF128075HMT120	12.0±20%	10.2	11.7	10.0	19.5	2.50
GAFF128075HMT150	15.0±20%	12.0	13.8	9.30	16.0	2.50
GAFF128075HMT180	18.0±20%	14.5	16.7	8.50	14.5	2.50
GAFF128075HMT220	22.0±20%	15.5	17.8	8.00	12.0	2.50
GAFF128075HMT270	27.0±20%	23.0	26.5	7.00	11.4	2.50
GAFF128075HMT330	33.0±20%	28.3	32.5	6.00	10.6	2.50
GAFF128075HMT390	39.0±20%	31.3	36.0	5.50	9.00	2.50
GAFF128075HMT470	47.0±20%	40.0	46.0	5.00	8.20	2.00
GAFF128075HMT560	56.0±20%	60.0	69.0	4.00	7.50	2.00

GAFF160070H SERIES

规格型号 Part Number	初始电感 (μ H)	DCR (m Ω)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF160070HMT1R0	1.00±20%	0.89	1.05	33.0	66.0	/
GAFF160070HMT1R5	1.50±20%	1.35	1.55	30.0	49.0	/
GAFF160070HMT2R2	2.20±20%	1.90	2.20	25.0	40.0	/
GAFF160070HMT3R3	3.30±20%	2.68	3.10	23.0	34.0	/
GAFF160070HMT4R7	4.70±20%	3.46	4.00	20.0	32.0	/
GAFF160070HMT5R6	5.60±20%	4.50	5.20	18.0	26.0	/
GAFF160070HMT6R5	6.50±20%	5.48	6.30	16.0	23.0	/
GAFF160070HMT8R2	8.20±20%	7.15	8.25	15.0	21.0	/
GAFF160070HMT100	10.0±20%	8.70	10.0	13.0	18.0	/
GAFF160070HMT150	15.0±20%	12.3	14.2	11.0	17.0	/
GAFF160070HMT220	22.0±20%	20.3	23.5	8.50	14.0	/

GAFF160070H SERIES



规格型号 Part Number	初始电感 (μ H)	DCR (m Ω)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF182090HMT1R8	0.82 \pm 20%	0.54	0.62	41.5	88.0	4.00
GAFF182090HMT2R0	1.30 \pm 20%	0.85	1.00	36.0	67.0	4.00
GAFF182090HMT2R7	2.00 \pm 20%	1.20	1.38	32.5	58.0	4.00
GAFF182090HMT3R6	2.70 \pm 20%	1.58	1.82	31.5	50.0	4.00
GAFF182090HMT4R7	3.60 \pm 20%	2.20	2.60	25.0	43.0	4.00
GAFF182090HMT5R6	4.70 \pm 20%	2.85	3.40	22.5	39.0	4.00
GAFF182090HMT6R8	5.60 \pm 20%	3.18	3.70	21.0	35.0	4.00
GAFF182090HMT8R5	6.80 \pm 20%	4.10	4.70	18.5	31.0	4.00
GAFF182090HMT100	8.50 \pm 20%	4.82	5.55	18.0	28.0	4.00
GAFF182090HMT150	10.0 \pm 20%	6.00	6.90	16.0	26.0	4.00
GAFF182090HMT220	15.0 \pm 20%	8.20	9.43	14.0	22.0	3.20
GAFF182090HMT330	22.0 \pm 20%	12.1	14.1	11.0	17.5	3.20
GAFF182090HMT470	33.0 \pm 20%	20.0	23.0	8.50	14.0	3.20
GAFF182090HMT560	47.0 \pm 20%	33.7	38.8	6.80	11.5	3.20
GAFF182090HMT680	56.0 \pm 20%	35.8	41.2	6.50	10.8	3.20

GAFF160070H SERIES

规格型号 Part Number	初始电感 (μ H)	DCR (m Ω)		温升电流 I _{rms} (A)	饱和电流 I _{sat} (A)	table
		典型值Typ.	最大值Max.			
GAFF220120HMT3R3	3.30 \pm 20%	1.03	1.20	32.0	70.0	4.00
GAFF220120HMT4R7	4.70 \pm 20%	1.52	1.75	30.0	58.0	4.00
GAFF220120HMT6R8	6.80 \pm 20%	2.33	2.70	26.0	48.0	4.00
GAFF220120HMT8R2	8.20 \pm 20%	2.78	3.20	24.0	45.0	4.00
GAFF220120HMT100	10.0 \pm 20%	3.37	3.88	21.0	40.0	4.00
GAFF220120HMT120	12.0 \pm 20%	4.17	4.80	19.5	37.0	4.00
GAFF220120HMT150	15.0 \pm 20%	4.73	5.45	18.0	32.0	4.00
GAFF220120HMT220	22.0 \pm 20%	7.15	8.25	15.0	27.0	4.00
GAFF220120HMT330	33.0 \pm 20%	11.6	13.5	11.5	22.0	4.00
GAFF220120HMT390	39.0 \pm 20%	17.2	19.8	9.50	20.5	3.50
GAFF220120HMT470	47.0 \pm 20%	18.6	21.4	9.00	18.5	3.50
GAFF220120HMT560	56.0 \pm 20%	20.2	23.3	8.20	17.0	3.50
GAFF220120HMT680	68.0 \pm 20%	26.3	30.3	7.50	15.0	3.20
GAFF220120HMT820	82.0 \pm 20%	29.3	33.7	7.00	13.8	3.20
GAFF220120HMT101	100 \pm 20%	35.5	40.8	6.10	12.5	3.20


● 包装规范 Package Specification

卷盘 Reel



项目 Item	A	C	D	E	E'
产品系列 Part No.	(mm)	(mm)	(mm)	(mm)	(mm)
GAFF069030H	330	13.0	100	16.5	20.5
GAFF069040H	330	13.0	100	16.5	20.5
GAFF069050H	330	13.0	100	16.5	20.5
GAFF102030H	330	13.0	100	24.5	28.5
GAFF102040H	330	13.0	100	24.5	28.5
GAFF102050H	330	13.0	100	24.5	28.5
GAFF102060H	330	13.0	100	24.5	28.5
GAFF128035H	330	13.0	100	24.5	28.5
GAFF128050H	330	13.0	100	24.5	28.5
GAFF128065H	330	13.0	100	24.5	28.5
GAFF128075H	330	13.0	100	24.5	28.5
GAFF160070H	330	13.0	100	32.5	36.5
GAFF182090H	330	13.0	100	32.5	36.5
GAFF220120H	330	13.0	100	44.5	48.5

载带 Carrier ttape



项目 Item	A0	B0	K0	P0	P	W	QTY. (PCS/REEL)
产品系列 Part No.	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
GAFF069030H	7.05	7.20	3.40	4.00	12.0	16.0	1500
GAFF069040H	7.30	7.55	4.80	4.00	12.0	16.0	1000
GAFF069050H	7.30	7.50	5.50	4.00	12.0	16.0	1000
GAFF102030H	10.8	11.0	4.00	4.00	16.0	24.0	800
GAFF102040H	10.8	11.3	5.00	4.00	16.0	24.0	800
GAFF102050H	10.8	11.3	5.70	4.00	16.0	24.0	700
GAFF102060H	10.8	11.3	6.30	4.00	16.0	24.0	400
GAFF128035H	13.7	13.7	4.4±0.2	4.00	16.0	24.0	400
GAFF128050H	14.0	14.0	5.80	4.00	16.0	24.0	400
GAFF128065H	13.6	13.7	7.00	4.00	16.0	24.0	400
GAFF128075H	13.6	13.7	7.80	4.00	16.0	24.0	300
GAFF160070H	16.6	16.5	7.20	4.00	20.0	32.0	200
GAFF182090H	19.4	18.8	10.5	4.00	32.0	32.0	150
GAFF220120H	23.5	23.5	13.1	4.00	32.0	44.0	120

●可靠性测试要求 Reliability test requirements

序号 No.	试验项目 Test Item	参考标准 Reference Standard	试验方法 Test Method	测试数量 Quantity
1	试验前后电气特性测试 Measure electrical characteristics before and after test	产品规格书 Specification	参照产品规格书 Refer to the specification	所有认证的产品 All of certified products
2	外观尺寸 External dimension	/	参照产品规格书 Refer to the specification	10Pcs
3	预处理 Pretreatment	/	3次模拟回流焊, 外观和电气性能符合规格书要求。 After 3 times reflow, external and electrical characteristics also meet to the specification	30Pcs
4	印字检查 Check the printing	/	3M 胶纸进行粘附试验, 粘 5 次后再进行检查, 无外观不良, 产品印字无掉缺、清晰可读 Use 3M adhesive paper adhesion test, stick 5 times and then check, no bad appearance, product printing without missing, clear and readable	10Pcs
5	寿命试验 Operating life test	MIL-STD-202G method 108	85°C环境下, 加载额定电流, 持续1000 小时, 产品外观、电性符合规格要求 At 85°C, the rated current is loaded for 1000 hours, the appearance and electrical characteristics meet the specifications	30Pcs
6	恒定湿热试验 Humidity Bias	MIL-STD-202G method 103	温度: 85°C/湿度: 85% RH, 持续1000 小时, 累计腐蚀面积小于10%, 产品外观、电性符合规格要求 85°C&85%RH, lasting 1000 hours, cumulative corrosion area is less than 10%, the appearance and electrical characteristics meet the specifications	30Pcs
7	冷热冲击试验 Temperature shock	MIL-STD-202G method 107	低温: -40°C/高温: 125°C, 停留时间: 15 分钟, 转换时间: 10 秒钟, 冲击次数: 100 次, 产品外观、电性符合规格要求 -40°C&125°C, residence time: 15 minutes, conversion time: 10 seconds, impact times: 100 times, product appearance, electrical characteristics meet to the specifications	30Pcs
8	高温存储 High temperature storage	MIL-STD-202G method 108	125°C or 产品最高工作温度, 1000 小时, 产品外观、电性符合规格要求 At 125°C or the maximum working temperature of the product, 1000 hours, the appearance and electrical characteristics meet the specifications	30Pcs
9	低温储存 Low temperature storage	IEC68-2-1	-40°C or 产品最低工作温度, 1000 小时, 产品外观、电性符合规格要求 At -40°C or the minimum working temperature of the product, 1000 hours, the appearance and electrical characteristics meet the specifications	30Pcs
10	振动试验 Vibration	MIL-STD-202, method 204	加速度: 10 G, 频率: 10 ~ 55 ~ 10 Hz, X、Y、Z 三个方向振动, 每个方向 12次, 每个方向振动时间: 20 分钟, 产品外观、电性符合规格要求 Acceleration: 10 G, frequency: 10 ~ 55 ~ 10 Hz, X, Y, Z three directions vibration, each direction 12 times, each direction vibration time: 20 minutes, the product appearance, electrical requirements meet the specifications	10Pcs
11	可焊性试验 Solderability	J-STD-002	蒸汽老化试验 8 小时, 助焊剂活性: 0 级, 温度: 245°C ± 5°C, 50 倍放大镜下观察, 上锡面积大于等于95% Steam aging test for 8 hours, flux activity: 0, temperature: 245°C ± 5°C, observation under 50 times magnifying glass, tin area greater than or equal to 95%	10Pcs

● 可靠性测试要求 Reliability test requirements

序号 No.	试验项目 Test Item	参考标准 Reference Standard	试验方法 Test Method	测试数量 Quantity
12	端子强度试验 Terminal strength	EIA-945	1.大于 0805 封装尺寸 (20.32mm*12.7mm) , 1.0kgf/60±5s Larger than 0805 package size (20.32mm*12.7mm), 1.0kgf/60±5s 2.小于 0805 封装尺寸 (20.32mm*12.7mm) , 0.5kgf/60±5s Less than 0805 package size (20.32mm*12.7mm), 0.5kgf/60±5s	10Pcs
13	盐雾试验 Salt spray test	EIA-364-26B ITEM B GB/T6461-2002	盐雾浓度: 5%±1%, 试验温度: 35°C±2°C, PH 值: 6.5~7.2, 时间:24、48 小时各 1 组, 产品取出后, 在温水洗去盐渍, 常温下自然风干 1 小时, 再进行检查: 24 小时后, 按GB/T6461-2002 标准A~B 级外观允收; 48 小时后, 按GB/T6461-2002 标准A~E 级外观允收 Salt spray concentration: 5%±1%, test temperature: 35°C±2°C, PH: 6.5~7.2, time :24/48 hours each group, after taking out the product, wash the salt in warm water, natural air dry for 1 hour at normal temperature, and then check: After 24 hours, according to GB/T6461-2002 standard A ~ B appearance acceptable; After 48 hours, according to GB/T6461-2002 standard A to E appearance acceptable	10Pcs
14	包装跌落试验 Package drop test	ISTA 2A	试验条件: 1~9kg→76cm 9~18kg→61cm 18~27kg→46cm 27~45kg→30cm 试验方法: 外观、电性合格的一整箱产品按要求包装好, 根据重量相对应的高度按一角三棱六面自由落地的方式跌落 10 次。 试验要求: 包装有无破损; 产品外观、电性符合规格要求 Test method: A whole box of products with qualified appearance and electrical properties should be packed according to the requirements and dropped 10 times according to the height corresponding to the weight by the way of free fall on one corner, three edges and six sides. Test requirements: whether the packaging is damaged; The appearance and electrical properties of the product meet the specifications	1Carton